


# Xerox® AltaLink® Colour Multifunction Printer



C8030/C8035/C8045/C8055/C8070

AltaLink C8000 Series Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).



System Specification	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Speed</b>					
Colour / Black and White	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm	Up to 70 / 70 ppm
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 90,000 pages / month	Up to 110,000 pages / month	Up to 200,000 pages / month	Up to 300,000 pages / month	Up to 300,000 pages / month
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	5,000 to 12,000 pages	5,000 to 15,000 pages	8,000 to 20,000 pages	8,000 to 22,000 pages	10,000 to 40,000 pages
<b>Hard Drive / Processor / Memory</b>	Minimum 250 GB HDD / Intel® Atom™ Quad Core 1.91 GHz / 2 MB Cache / 8 GB system memory				
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, Wi-Fi Direct with optional Xerox® USB Wireless Adapter, Near Field Communication (NFC)				
<b>Controller Features</b>	Unified Address Book, Remote Control Panel, Configuration Cloning				
<b>Optional Controller</b>	Xerox® EX-c C8000 Print Server Powered by Fiery®				
<b>Copy and Print</b>					
<b>Copy and Print Resolution</b>	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 2400 dpi				
<b>First-Print-Out Time colour/black-and-white</b>	As fast as 6.5 / 5.3 seconds	As fast as 6.4 / 5.2 seconds	As fast as 6.5 / 5.3 seconds	As fast as 6.0 / 4.7 seconds	As fast as 4.7 / 4.0 seconds
<b>First-Copy-Out Time (from platen/warmed up state)</b>	As fast as 8.1 seconds / As fast as 6.7 seconds	As fast as 8.1 seconds / As fast as 6.7 seconds	As fast as 7.8 seconds / As fast as 6.4 seconds	As fast as 7.2 seconds / As fast as 5.7 seconds	As fast as 5.2 seconds / As fast as 4.9 seconds
<b>Page Description Language</b>	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, optional XML Paper Specification (XPS®)				
<b>Print Features</b>	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs				
<b>Mobile (Optional)</b>					
<b>Mobile Printing (optional)</b>	Xerox Mobile Print®, Xerox® Mobile Print Cloud, Xerox® Print Management and Mobility Suite				
<b>Mobile Printing Connectivity</b>	Apple® AirPrint®, Mopria® Certified, Mopria® Print Service Plug-in for Android™, @PrintByXerox, Xerox® Print Service Plug-in for Android™				
<b>Mobile Apps and Xerox® App Gallery</b>	Xerox® App Gallery: <b>Cloud Connector Apps:</b> Print and Scan to/from: Google Drive®, Microsoft® OneDrive®, Microsoft Office 365™, DropBox™ and Box® <b>Productivity Apps:</b> Xerox® Easy Translator Service <b>Device Management Apps:</b> QR Code <b>Scan Apps:</b> Xerox® Scanning App for DocuShare® See the full list of apps available in the Xerox® App Gallery at <a href="http://www.xerox.com/appgallery">www.xerox.com/appgallery</a> .				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Mobile (Optional)					
<b>Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service</b>	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.				
Scan					
<b>Standard Features</b>	<b>Destinations:</b> Scan to USB / Email / Network (FTP/SMB); <b>File Formats:</b> PDF, PDF/A, XPS, JPEG, TIFF; <b>Convenience Features:</b> Scan to Home, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR)				
<b>Optional Features</b>	ConnectKey® for DocuShare®, other solutions available through various Xerox Business Innovation Partners				
Fax					
<b>Standard Features</b>	Internet Fax, Fax Build Job, Network Server Fax Enablement				
<b>Optional Features</b>	Fax Forward to Email or SMB, Walk-up Fax (one-line and two-line options, includes LAN Fax)				
Security					
<b>Standard Features</b>	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions				
<b>Optional Features</b>	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET)				
Accounting					
<b>Standard Features</b>	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement				
<b>Optional Features</b>	Equitrac®, YSoft® Papercut®, other network accounting solutions available through various Xerox Business Innovation Partners				
Device Specification					
<b>Control Panel Languages</b>	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic				
Accessories					
<b>Optional</b>	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Horizontal Transport Kit BR Finisher (requires Horizontal Transport Kit) (optional with C8030, C8035, C8045, C8055, C8070) BR Booklet Maker Finisher (requires Horizontal Transport Kit) (optional with C8030, C8035, C8045, C8055, C8070) C-fold / Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (Work Surface recommended) Integrated Office Finisher (optional with C8030, C8035) Office Finisher LX (optional with C8030, C8035, C8045, C8055) Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Smart Card Enablement Kit EFI™ Fiery® Integrated Network Server Walk up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit XPS Print Option Kit <sup>1</sup>				
<b>Foreign Device Interface (FDI)</b>	Also known as Auxiliary Access Device, this is an interface to third party access control devices, such as coin machines and card readers.				
Electrical Requirements	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>North America</b>	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
<b>Europe</b>	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A				Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
Power Consumption	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Running (Average)</b>	110V: 653 watts 220V: 667 watts	110V: 687 watts 220V: 699 watts	110V: 740 watts 220V: 761 watts	110V: 787 watts 220V: 810 watts	110V: 942 watts 220V: 972 watts
<b>Standby Mode</b>	110V: 63 watts 220V: 61.5 watts	110V: 64 watts 220V: 61.6 watts	110V: 70.9 watts 220V: 70.5 watts	110V: 94.9 watts 220V: 81.5 watts	110V: 84.6 watts 220V: 81.6 watts
<b>Low Power Mode</b>	110V: 60 watts 220V: 57.7 watts	110V: 59.6 watts 220V: 57.3 watts	110V: 62.7 watts 220V: 60.2 watts	110V: 61.8 watts 220V: 60.3 watts	110V: 79.3 watts 220V: 76.9 watts
<b>Auto Off/Sleep Mode</b>	110V: 3.53 watts 220V: 3.84 watts (Default time to sleep mode = 2 minutes)	110V: 3.54 watts 220V: 3.78 watts (Default time to sleep mode = 2 minutes)	110V: 3.78 watts 220V: 3.63 watts (Default time to sleep mode = 2 minutes)	110V: 3.34 watts 220V: 3.49 watts (Default time to sleep mode = 2 minutes)	110V: 3.59 watts 220V: 3.85 watts (Default time to sleep mode = 2 minutes)
<b>Warm-up (from Off)</b>	As fast as 92 seconds				

## Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Power Consumption	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
Recovery from Low Power	As fast as 2 seconds				
Recovery from Sleep	As fast as 6.2 seconds				
<b>Operating Environment</b>					
Required Temperature Range	10 to 28° C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.9 dB(A) Standby: 3.32 dB(A)		Operating: 68.3 dB(A) Standby: 3.35 dB(A)		Operating: 71.3 dB(A) Standby: 3.31 dB(A)
<b>Dimensions and Weight</b>					
Base Configuration	Width: 640 mm Depth: 723.8 mm Height: 1,142.7 mm Weight: 151.9 kg				
With Integrated Office Finisher ( C8030, C8035)	Width: 662.6 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 158 kg				
With Office Finisher LX (with Booklet Maker)	Width: 1,182 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 177.2 kg				
Base Configuration with Business Ready (BR) Finisher	Width: 1,277 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 195.3 kg				
Base Configuration with BR Booklet Maker Finisher	Width: 1,429.2 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 212.3 kg				
Base Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit	Width: 1,664.2 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 264.4 kg				
Base Configuration with BR Booklet Maker Finisher, C-fold / Z-fold Unit and High Capacity Feeder	Width: 1,978.2 mm Depth: 732.8 mm Height: 1,142.7 mm Weight: 293.4 kg				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

System Certification/Regulatory Compliance					
<b>Certifications</b>	FCC Class A Compliant (US), ICES Class A Compliant (Canada) TUV Listed to "UL60950-1, Second Edition" TUV Certified to "CSA 22.2 No. 60950-1-07, Second Edition" CB Certified (IEC 60950-1, Second Edition) CE Mark ENERGY STAR® EPEAT (United States) EAC Wi-Fi Direct Certification WIFI Blue Angel GS Mark Genoa Bonjour Adobe PS FIPS140-2 Open SSL WI-Fi Alliance McAfee Section 508 Env. Choice (Canada) Citrix® Certified MEDITECH Mopria® Cert.* WHQL* Cerner* Ukrainian Cert.* IPv6 Ready* NOM cert. (Mexico)* BIS (India)* EAC (Russia)* SAP* Google cloud print* Common Criteria (IEEE 2600.2 standard) (undergoing evaluation) *In progress, refer to latest on-line product specifications document at <a href="http://www.xerox.com/AltalinkC8000Specs">www.xerox.com/AltalinkC8000Specs</a>				
<b>Paper Handling</b>	<b>AltaLink C8030</b>	<b>AltaLink C8035</b>	<b>AltaLink C8045</b>	<b>AltaLink C8055</b>	<b>AltaLink C8070</b>
Single-pass Duplex Automatic Document Feeder (DADF)					
<b>Capacity<sup>4</sup></b>	130 sheets				
<b>Speed</b>	Up to 80 pages per minute black-and-white and colour (simplex) Up to 139 images per minute (ipm) black-and-white and colour (duplex)				
<b>Paper Sizes Sensed</b>	85 x 125 mm to 297 x 431.8 mm				
<b>Weights</b>	60 to 128 gsm				
Bypass Tray					
<b>Capacity<sup>4</sup></b>	100 sheets				
<b>Sizes</b>	Custom Sizes: 89 x 98 mm to 320 x 483 mm				
<b>Weights</b>	60 to 300 gsm				
<b>Media Types</b>	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Cardstock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				
Trays 1 and 2 (Standard)					
<b>Capacity<sup>4</sup></b>	520 sheets each				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Trays 1 and 2 (Standard)	
<b>Sizes</b>	Tray 1: Custom Sizes: 140 x 182 mm to 297 x 432 mm short edge feed (SEF) Tray 2: Custom Sizes: 140 x 182 mm to SRA3 (SEF)
<b>Weights</b>	60 to 256 gsm
<b>Media Types</b>	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Cardstock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies
Four Tray Module (Trays 3 and 4) (Available on C8030/C8035)	
<b>Capacity<sup>4</sup></b>	Tray 3: 520 sheets Tray 4: 520 sheets
<b>Sizes</b>	Trays 3 and 4: 140 x 182 mm to SRA3 mm (SEF)
<b>Weights</b>	60 to 256 gsm
<b>Media Types</b>	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Cardstock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies
High Capacity Tandem Tray (Optional on C8030/C8035)	
<b>Capacity<sup>4</sup></b>	Tray 3: 867 sheets Tray 4: 1,133 sheets
<b>Sizes</b>	A4, JIS B5, Executive LEF
<b>Weights</b>	60 to 256 gsm
<b>Media Types</b>	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Plain Preprinted

## Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

<b>Envelope Tray (Optional - Replaces Tray 1)</b>					
<b>Capacity<sup>4</sup></b>	Up to 60 envelopes				
<b>Sizes</b>	Monarch, DL, C5 Custom Sizes: 98 x 148 mm to 162 x 241 mm				
<b>Weights</b>	75 to 90 gsm				
<b>High Capacity Feeder (HCF) (Optional with all models)</b>					
<b>Capacity<sup>4</sup></b>	2,000 sheets				
<b>Sizes</b>	Standard Sizes: A4 or B5 LEF				
<b>Weights</b>	55 to 256 gsm				
<b>Total Capacity</b>					
<b>Device Total Capacity<sup>4</sup></b>	Four Tray Module: 2,180 sheets Four Tray Module with High Capacity Feeder: 4,180 sheets High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capacity Feeder: 5,140 sheets				
<b>Finishing</b>	<b>AltaLink C8030</b>	<b>AltaLink C8035</b>	<b>AltaLink C8045</b>	<b>AltaLink C8055</b>	<b>AltaLink C8070</b>
<b>Output Trays (Standard) (Dual Offset Catch Trays not available with Integrated Office Finisher and limited to one with LX and BR Finishers)</b>					
<b>Stacking Tray Capacity<sup>4</sup></b>	Dual Offset Catch Tray - Up to 250 sheets each Left Side Face up Tray - Up to 100 sheets				
<b>Integrated Office Finisher (Optional with C8030/C8035)</b>					
<b>Stacking Tray</b>	500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3				
<b>Sizes</b>	89 x 98 mm to 297 x 432 mm				
<b>Weights</b>	60 to 256 gsm				
<b>Stapling</b>	Single Auto-Stapling: 50 sheets maximum: A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: A3 / B4 size sheets (less than 90 gsm or (2) 220 gsm covers)				
<b>Office Finisher LX (Optional with C8030/C8035/C8045/C8055)</b>					
<b>Stacking Tray Capacity<sup>4</sup></b>	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4)				
<b>Stacking Tray Sizes</b>	210 x 182 mm to 297 x 432 mm				
<b>Weights</b>	60 to 256 gsm				
<b>Multiposition Stapling</b>	50 sheets of 90 gsm				
<b>Hole Punch (Optional)</b>	Europe 2-4 Hole Punch				
<b>Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)</b>					
<b>Top Tray Capacity<sup>4</sup></b>	40 booklets (2-15 sheets per booklet – 80 gsm or less)				
<b>Sizes</b>	A4 SEF B4 SEF A3 SEF				
<b>Saddle-Stitch Stapling</b>	2-15 sheets / 8-60 page booklet 60 x 90 gsm				
<b>Score / Crease</b>	1-15 sheets / unstapled				
<b>Optional Business Ready (BR) Finisher (Requires Horizontal Transport Kit)</b>					
<b>Capacity<sup>4</sup></b>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) A3 or 200 sets (single-position staple) A4				
<b>Sizes</b>	B5 to A3 for stacking B5 to A3 for stapling				
<b>Weights</b>	60 to 300 gsm (coated and uncoated)				
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported				
<b>Hole Punch</b>	Europe 2-4-hole punch 4-hole "Swedish" punch (optional)				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Optional BR Booklet Maker Finisher (Requires Horizontal Transport Kit)					
<b>Capacity<sup>4</sup></b>	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3				
<b>Sizes</b>	A6 to A3 for stacking B5 to A3 for stapling				
<b>Weights</b>	60 to 300 gsm (coated and uncoated)				
<b>Stapling</b>	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm A3, A4, B4 and B5 sizes supported				
<b>Hole Punch</b> Europe	2-4-hole punch 4-hole “Swedish” punch (optional)				
<b>Booklet Maker</b>	Saddle-stitch 2 to 15 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets A3, A4 supported				
C-fold / Z-fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)					
<b>Types</b>	C-fold, Z-fold and Z-half-fold				
<b>Capacity<sup>4</sup></b>	40 sheets				
<b>Sizes</b>	A4 SEF only A3 only				
<b>Weights</b>	64 to 90 gsm				
<b>Output Trays</b>	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold				
Convenience Stapler (Optional - Work Surface Recommended)					
<b>Capacity<sup>4</sup></b>	50-sheet stapling 5,000 staples Requires separate power outlet				
Copy	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>First-Copy-Out Time</b> (from platen/warmed up Colour / Black and White)	As fast as 8.1 seconds / As fast as 6.7 seconds	As fast as As fast as 8.1 seconds / As fast as 6.7 seconds	As fast as As fast as 7.8 seconds / As fast as 6.4 seconds	As fast as As fast as 7.2 seconds / As fast as 5.7 seconds	As fast as As fast as 5.2 seconds / As fast as 4.9 seconds
<b>Sides (input:output)</b>	1-1, 1-2, 2-2, 2-1				
<b>Quantity</b>	1 to 9,999				
<b>Resolution(max)</b>	Up to 600 x 600 dpi				
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments				
<b>Concurrency</b>	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)				
<b>Copy Features</b>	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Transparencies				
Print	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Resolution</b>	Up to 1200 x 2400 dpi				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Print	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Print Features</b>	Application Defaults Banner Sheet Enable / Disable Custom Colour Options (Colour By Words) Bi-directional Real-time Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute Sample Set Saved Job (colour jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default)				
<b>Print from USB</b>	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL Colour jobs can be printed as black-and-white				
<b>Operating Systems</b>	Microsoft® Windows® XP SP3 (32- and 64-bit) Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Vista SP2 (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86 Ubuntu® 14.04 x64 openSUSE® 13.1 x64				
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Bonjour® / AirPrint® IPv6 Secure FTP Most protocols not in use can be disabled				
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS				
<b>Font Capability</b>	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts				
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.				
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.				
<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.				
<b>Unified Address Book for Fax, Internet Fax, Email and Scan to...</b>					
<b>Features</b>	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported				
Scan	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Concurrency</b>	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)				
<b>Input Speed</b>	Up to 80 page per minute black-and-white and colour (simplex) Up to 139 images per minute (ipm) black-and-white and colour (duplex)				
<b>Resolution</b>	72 x 72 dpi to 600 x 600 dpi				
<b>Bit Depth</b>	1-bit (black-and-white), 8-bit (greyscale), 24-bit (colour)				
<b>Maximum Scan Area</b>	A3				



# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Scan	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Scan Template Management</b>	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers Confirmation sheet options				
<b>Network Protocols</b>	sFTP, FTP, SMB, HTTP, HTTPS				
<b>File Compression</b>	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Linearised PDF / PDF/A				
<b>Document Management Fields (Metadata)</b>	Features only available in Network Scan to File Templates: <ul style="list-style-type: none"> <li>• 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations</li> <li>• Customised fields viewed on user interface for variable data input</li> </ul>				
<b>Scan Features</b>	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)				
<b>Scan to Email (Standard)</b>					
<b>Scan Features</b>	<ul style="list-style-type: none"> <li>• Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options</li> <li>• Scan to Email S/MIME Encryption</li> <li>• Email signing (requires Smart Card option)</li> <li>• Auto send to self</li> </ul>				
<b>Directory Access</b>	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Device Address Book				
<b>Scan to... (Standard)</b>					
<b>Features</b>	Scan to USB Scan to Network Folder (uses Unified Address Book entries) Scan to Home Scan to USB Scan to Network Scan to Email				
<b>Workflow Scanning (Optional)</b>					
<b>Scanning Software</b>	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2				
<b>Scanning Apps and Xerox® App Gallery</b>	Scan to/from: Dropbox™, Google Drive™, Microsoft® OneDrive®, Microsoft Office 365™ and Box® See the full list of apps available in the App Gallery: <a href="http://www.xerox.com/appgallery">www.xerox.com/appgallery</a> .				
Security	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Features</b>	<ul style="list-style-type: none"> <li>• Expanded Authentication <ul style="list-style-type: none"> <li>- Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008, Windows server 2012), NDS, LDAP authentication</li> <li>- Local Authentication (internal database)</li> <li>- Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET</li> <li>- Secure Data</li> <li>- Digitally signed PDF (when using Smart Card authentication)</li> <li>- Encrypted and authentication to SMTP server for Scan to Email</li> <li>- Encrypted / Password Protected PDF (when using Email and Network Scan Templates only)</li> <li>- Secure Print (up to 10 digit PIN or Network Authentication)</li> <li>- Immediate Image Overwrite / Securely delete jobs using approved algorithms</li> <li>- On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>- FIPS 140-2 256 bit Hard Disk Encryption, TLS, IPPS, HTTPS, SFTP, SNMPv3</li> </ul> </li> <li>• Expanded Authorisation <ul style="list-style-type: none"> <li>- SA access based on network credentials</li> <li>- Authorisation per user per service</li> <li>- User Permissions required to access Print and Print Features (e.g. colour access, or time restrictions) reflects in the print driver</li> <li>- Secure Network Access</li> </ul> </li> <li>• IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, SFTP</li> <li>- McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional)</li> <li>• Common Criteria Certification ISO 15408 (undergoing evaluation)</li> </ul>				
<b>Xerox® Integrated RFID Card Reader E1.0 (Optional kit)</b>	Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel.				
Fax	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Network Server Fax Features</b>					
<b>Compatibility</b>	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Fax	AltaLink C8030	AltaLink C8035	AltaLink C8045	AltaLink C8055	AltaLink C8070
<b>Network Server Fax Features</b>					
<b>Maximum Scan Area</b>	A3				
<b>Fax Send Features</b>	One- or Two-sided Scanning (up to A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)				
<b>Fax Print Features</b>	One- or Two-sided Printing, Staple, Secure Print				
<b>Transmission Resolution</b>	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi				
<b>Internet Fax Features</b>					
<b>Compatibility</b>	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients				
<b>Directory Access</b>	Utilises the Unified Address Book				
<b>Send/Receive</b>	Multi-page TIFF, Image only PDF				
<b>Resolution</b>	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)				
<b>Network Protocols</b>	SMTP (send), POP3 (receive)				
<b>Compliance</b>	ITU-T T.37 compliant				
<b>Walk-up Fax Features (Customer-installable) – 1 and 2 lines</b>					
<b>Compatibility</b>	ITU (CCITT) Group 3				
<b>Speed / Modems</b>	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilising T38 (optional)				
<b>Compression / Speed</b>	MH/G3, MMR/SG3				
<b>Resolution</b>	<b>Walkup Send:</b> Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi <b>Receive:</b> Accepts all sizes				
<b>Fax Send Features</b>	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity)				
<b>Fax Receive Features</b>	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay				
<b>Fax Forward</b>	Forward to Email or SMB Location Fax Forward on Receive Only				
<b>Fax Reports</b>	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report				
<b>Directory Access</b>	Utilises the Unified Address Book Group fax available				
<b>Auto Redial</b>	Up to 14 attempts (per country requirements) 1 to 25 minute intervals				
<b>Auto Resend</b>	Up to 5 attempts				
<b>Device Management</b>					
<b>Management Support</b>	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2				
<b>Xerox® CentreWare® Web</b>	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> <li>• Works with any SNMP-managed printer from any manufacturer.</li> <li>• Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management.</li> <li>• Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher.</li> <li>• CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®</li> </ul>				

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

Device Management	
<b>Novell NDPS/NEPS</b>	Server gateway application: centralized management tool.
<b>Xerox® Device Manager</b>	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> <li>• Device monitoring and troubleshooting</li> <li>• Extensive reporting and discovery of new devices</li> <li>• Usage collection, chargeback and billing capabilities</li> </ul>
<b>Xerox® Device Types for SAP Environment</b>	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. As an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>
<b>Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)</b>	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>
<b>Xerox® Barcode Pro PS (optional)</b>	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at <a href="http://www.office.xerox.com/software-solutions">www.office.xerox.com/software-solutions</a>
Xerox® Embedded Web Server - Integrated Device Web Pages Provided by the Device	
<b>Device Status</b>	Web server embedded in Network Controller: <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Alerts</li> </ul> Remote Control Panel
<b>Job Submission</b>	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Internet Explorer 10.x, 11.x Safari 8.x, 9.x, 10.x Mozilla Firefox 35.x through 51.x Opera 27.x through 41.x Chrome 4.0x through 56.x
<b>Support</b>	Install print / scan drivers and online support available via web page
<b>Languages Supported</b>	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
<b>Automated Meter Reading (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automated Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox®, allowing for problems to be solved faster, either by the user or by support agents using remote service tools, increasing uptime.
Accounting	
Xerox® Standard Accounting (Standard)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group accounts (Department)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>• Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements with the addition of HTTPS protocol support</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>• Interface with third party accounting terminal for accounting user interface</li> </ul>
EFI™ Fiery® Integrated Network Server(Optional)	
<b>Processor</b>	2.9 GHz, Intel® Pentium® G850 Dual-Core
<b>Memory (ESS)</b>	1 GB
<b>System Disk</b>	500 GB HDD
<b>Page Description Language</b>	PostScript v 3020

# Xerox® AltaLink® C8030/C8035/C8045/C8055/C8070 Colour Multifunction Printer

## EFI™ Fiery® Integrated Network Server(Optional)

<b>Features</b>	Fiery Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management Job Preview Job Merge Change Job Properties PANTONE® Colour Tables Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm – Variable Data capabilities Booklet Maker – booklet wizard to create booklets Print from USB flash drive Secure Erase EFI PrintMe Fiery® VUE Calibration Secure Printing User Authentication Drag and Drop job Management with CWS Importing Jobs
<b>Connectivity</b>	10Base-T/100Base-TX/1000Base-T Ethernet
<b>Optional</b>	Fiery Options Bundle (Spot On, Auto Trapping, Hot Folders, Virtual Printers) Network Switch to connect both printer and Fiery Server to Network

Supplies	Description	Quantity	Part Number
<b>Supplies</b>			
<b>Toner Cartridge (Sold)<sup>5</sup></b>	Black	26,000 pages	006R01697
	Cyan	15,000 pages	006R01698
	Magenta	15,000 pages	006R01699
	Yellow	15,000 pages	006R01700
<b>Transfer Belt Cleaner</b>	1 Assembly	160,000 pages	001R00613
<b>Second Bias Transfer Roll</b>	1 Assembly	200,000 pages	008R13064
<b>Staple Cartridges</b>	for BR Finisher, Integrated Office Finisher, Office Finisher LX and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge	008R13177
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
<b>Staple Refills</b>	for Integrated Office Finisher, Office Finisher LX and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
<b>Xerox® Smart Kit®</b>			
<b>Drum Cartridge<sup>6</sup></b>	1 Cartridge per Colour	125,000	013R00662
<b>Waste Toner Container with Suction Filter<sup>7</sup></b>	1 Cartridge	43,000	008R13061

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> XPS option is required to print XPS files

<sup>4</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>5</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

<sup>6</sup> Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 30% colour / 70% black-and-white pages.

<sup>7</sup> Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

[www.xerox.com](http://www.xerox.com)